

SKAPS GE-200
HEAVY WEIGHT
NON-WOVEN GEOTEXTILE



SKAPS INDUSTRIES

335 Athena Drive,
Athens, GA 30601
Ph: (706)-354-3700
Fax: (706)-354-3737
Email: contact@skaps.com

SKAPS GE-200 is a needle-punched nonwoven geotextile made of 100% polypropylene staple fibers, which are formed into a random network for dimensional stability. SKAPS GE-200 resists ultraviolet deterioration, rotting, biological degradation, naturally encountered basics and acids. Polypropylene is stable within a pH range of 2 to 13.

SKAPS GE-200 conforms to the physical property values listed below:

PROPERTY	TEST METHOD	ENGLISH (MARV ²)	METRIC (MARV ²)
Weight	ASTM D 5261	20 oz/yd ²	675 g/m ²
Grab Tensile Strength	ASTM D 4632	450 lbs	1.99 kN
Grab Elongation	ASTM D 4632	50%	50%
Trapezoid Tear Strength	ASTM D 4533	125 lbs	0.55 kN
CBR Puncture Resistance	ASTM D 6241	1437 lbs	1.67 kN
UV Resistance	ASTM D 4355	70%/500 hrs.	70%/500 hrs.

At time of manufacturing. Handling may change these properties.

This information is provided for reference purposes only and is not intended as a warranty or guarantee. SKAPS assumes no liability in connection with the use of this information.